



17 Series LCD Monitors



Model	K517s	K717s	K917s
Panel Size	15"	17"	19"
Display Area	12.0"x9.0"	13.3"x10.6"	14.8"x11.6"
Pixel Pitch	0.297mm	0.264mm	0.294mm
Brightness (typ.)	250cd/m ²	260cd/m ²	250cd/m ²
Contrast Ratio (typ.)	400:1	450:1	450:1
Video Response	25ms	16ms	16ms
Horizontal Viewing Angle	120°	140°	140°
Vertical Viewing Angle	100°	140°	140°
Optimum Resolution	1024x768	1280x1024	1280x1024
Display Colors	262,144	16.2M	16.7M
Horizontal Freq.	31 - 60kHz	31 - 80kHz	31 - 80kHz
Vertical Freq.	60 - 75Hz	60 - 75Hz	60 - 75Hz
Bandwidth	80MHz	135MHz	135MHz
Compatibility	PC, Mac	PC, Mac	PC, Mac
Interface	Analog D-Sub	Analog D-Sub	Analog D-Sub
Power			
Power Supply	Integrated	Integrated	Integrated
Standby Consumption	<3watts	<3watts	<3watts
Maximum Consumption	36watts	40watts	50watts
Dimensions / Weight			
Physical Dimensions (WxDxH)	13.7"x6.8"x13.4"	14.9"x7.5"x14.9"	16.8"x8.3"x16.9"
Packaging (WxDxH)	15.6"x4.9"x16.7"	17.1"x5.5"x19.5"	19.1"x5.5"x20.7"
Net/Gross Weight	6.4lbs. / 7.5lbs.	8.4lbs. / 9.9lbs.	10.6lbs. / 12.8lbs.
Features			
Plug & Play	Yes	Yes	Yes
Auto Adjustment	Yes	Yes	Yes
Integrated Speakers	No	No	No
Control Buttons	4 keys	4 keys	4 keys
Tilt Angle	+30° / -5°	+30° / -5°	+30° / -5°
Kensington® Lock Port	Yes	Yes	Yes
VESA® Wall Mount Option	Yes	Yes	Yes

Regulations CE, FCC DOC, CCC, CB, UL/CUL, TUV/GS, BSMI, S-Mark

Visualize The Value

www.kdsusa.com | 1-800-283-1311

© KDS Inc., 2005. All rights reserved. Information on this publication subject to change without notice.



04-18-05